

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29CFR 1910.1200

Rev. 06/02/06

TIN/LEAD ALLOYS

SRA

56 LEONARD ST., SUITE #2
FOXBORO, MA 02035

Phone: 508-543-4111
Infotrac Emergency : 1-800-535-5053

1. PRODUCT INGREDIENTS

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Weight %</u>	<u>Permissible Air Concen.(mg/cu.m.)</u>		<u>SARA Title III Sect.313Chem.</u>
			OSHA	ACGIH	
TIN	7440-31-5	0-100	2.0	2.0	NO
LEAD	7439-92-1	0-100	0.05	0.15	YES

No other hazardous material is present in concentration greater than 1%(.01% for carcinogens)

2. PHYSICAL DATA

Material is SOLID	Appearance and Odor SILVER-WHITE METAL		
Melting Point METAL 179-312°F	Boiling Point >1300°C	Specific Gravity 7.3-11.3	Vapor Density N/A
Solubility in Water INSOLUBLE	Vapor Pressure N/A	Evaporation Rate N/A	pH N/A

3. FIRE AND EXPLOSION DATA

Flash Point METAL N/A CORE - 300°F	Flammable Limits N/A	Auto Ignition Temp. N/A
--	-------------------------	----------------------------

Unusual Fire and Explosion Hazards

MOLTEN METALS PRODUCE FUME OR VAPOR THAT MAY BE TOXIC AND/OR RESPIRATORY IRRITANTS. REACTS VIOLENTLY WITH OXIDIZING AGENTS.

Fire Extinguishing Agents Recommended

USE CO2 OR DRY CHEMICAL ON SURROUNDING FIRE

Fire Extinguishing Agents to Avoid

DO NOT USE WATER ON FIRE WHERE MOLTEN METAL IS PRESENT

Special Fire Fighting Precautions

USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS AND FULL BODY PROTECTIVE CLOTHING.

Spill or Leak

ANY METHOD THAT KEEPS DUST TO A MINIMUM IS ACCEPTABLE. VACUUMING IS PREFERRED. USED OF APPROVED RESPIRATORY PROTECTION WHERE POSSIBILITY OF DUST/FUME EXPOSURE EXISTS. DO NOT USE COMPRESSED AIR FOR CLEANING.

Personal Hygiene

AVOID INHALATION OR INGESTION. PRACTICE GOOD HOUSEKEEPING AND PERSONAL HYGIENE PROCEDURES. A SHOWER IS RECOMMENDED IF SIGNIFICANT DUST EXPOSURE OCCURS.

Engineering Controls

LOCAL EXHAUST VENTILATION IS RECOMMENDED FOR DUST AND/OR FUME GENERATION OPERATIONS WHERE AIRBORNE EXPOSURES MAY EXCEED PERMISSIBLE AIR CONCENTRATIONS.

Storage

GENERAL STORAGE PROCEDURES ACCEPTABLE.

Special Precautions, Procedures, Label Instruction

SPECIAL ATTENTION IS DRAWN TO THE REQUIREMENTS OF THE OSHA LEAD STANDARD (1910.1025) AND RESPIRATOR STANDARD (1910.134) SHOULD AIRBORNE EXPOSURES EXCEED THE OSHA ACTION LEVEL OR PEL.

6. PERSONAL PROTECTIVE EQUIPMENT**Respiratory Protection**

WHERE AIRBORNE EXPOSURES MAY EXCEED OSHA/ACGIH PERMISSIBLE AIR CONCENTRATIONS. THE MINIMUM RESPIRATORY PROTECTION RECOMMENDED IS A NEGATIVE PRESSURE AIR PURIFYING RESPIRATOR WITH CARTRIDGES THAT ARE NIOSH/MSHA APPROVED AGAINST DUST, FUMES AND MISTS HAVING A TWA NOT LESS THAN 0/05 MG/CU M.

Eyes and Face

SAFETY GLASSES RECOMMENDED WHERE THE POSSIBILITY OF GETTING DUST PARTICLES IN EYES EXISTS OR WHEN HANDLING MOLTEN METAL.

Other Clothing and Equipment

GLOVES AND OTHER PROTECTIVE CLOTHING RECOMMENDED IF SKIN CONTACT IS APPRECIABLE.

7. REACTIVITY DATA

Stability: STABLE

Conditions to Avoid: NOT APPLICABLE

Incompatibility: STRONG OXIDIZERS MAY CAUSE VIOLENT REACTION

Hazardous Decomposition Products: AT TEMPERATURES ABOVE THE MELTING POINT, TOXIC FUMES OR VAPORS MAY BE EMITTED.

8. ENVIRONMENTAL

Regulated by DOT? NO

Waste Disposal Method(DISPOSER MUST COMPLY WITH FEDERAL, STATE AND LOCAL DISPOSAL OR DISCHARGE LAWS)

IF HAZARDOUS UNDER 40 CFR261, SUBPARTS B AND C, MATERIAL MUST BE TREATED OR DISPOSED IN A FACILITY MEETING THE REQUIREMENTS OF 40 CFR254 OR 265. IF NON-HAZARDOUS, MATERIAL SHOULD BE DISPOSED IN A FACILITY MEETING THE REQUIREMENTS OF 40 CFR257.

RCRA Status of Unused Material

IF DISCARDED IN UNALTERED FORM, MATERIAL SHOULD BE TESTED TO DETERMINE IF IT MUST BE CLASSIFIED AS A HAZARDOUS WASTE FOR DISPOSAL PURPOSES. UNDER SPECIFIC CIRCUMSTANCES, APPLICATION CAN BE MADE TO THE EPA ADMINISTRATOR TO HAVE A PARTICULAR WASTE DESIGNATED NON-HAZARDOUS.

9. ADDITIONAL INFORMATION

Precautions to be taken in handling and storing: NONE

Other Precautions: NONE

10. TRANSPORTATION REQUIREMENTS

D.O.T. HAZARD CLASS	N/A
D.O.T. PROPER SHIPPING NAME	*
D.O.T. LABELS REQUIRED	N/A
D.O.T. PLACARD REQUIRED	N/A
UN/NA CODE	N/A

*THIS PRODUCT IS NOT REGULATED BY THE D.O.T. AS SHIPPED.
THIS MATERIAL IS ONLY REGULATED BY THE D.O.T. IF IN A POWDER FORM WITH A PARTICLE SIZE LESS THAN 100 MICROMETERS. (0.0040 INCHES)

11. CERCLA INFORMATION

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO THE RELEASE REQUIREMENTS OF SECTION 302:

CHEMICAL NAME:	LEAD	
REPORTABLE QUANTITY (LBS)	1.0	CERCLA STATUTORY RQ

SPILLS TO BE ENVIRONMENT EXCEEDING THE REPORTABLE QUANTITY IN ANY 24 HOUR PERIOD MUST BE REPORTED TO THE NATIONAL RESPONSE CENTER (1-800-424-8802). NO REPORTING OF RELEASES OF THE HAZARDOUS SUBSTANCE IS REQUIRED IF THE DIAMETER OF THE PIECES OF THE SOLID METAL RELEASED IS EQUAL TO OR EXCEEDS 100 MICROMETERS (0.400 INCHES).

This Material Safety Data Sheet is offered for your information, consideration and investigation. SRA provides no warranties, either expressed or implied, and assumes no responsibilities for the accuracy or completeness of the data contained in this document. The data in this Material Safety Data Sheet relates to this product and does not relate to use in combination with any other material or in any process.